

# JARRETT E SERIES SLASHERS\*

*"I've used many Jarrett implements in the 30 yrs I've been contracting, and will continue to do so."*

— J. Formiatti, Landscape contractor



The EHD180 slasher



The EHD180G slasher (with optional galvanised deck and wheel kit)

## General construction

- 5mm steel deck sheet
- 12mm steel reinforced gearbox plate (17mm total thickness for gearbox mounting)
- Obstruction free top deck (no debris collection points)
- Obstruction free cutting chamber
- Strong RHS linkage frame with clevis hitch and Category 2 lifting pins
- Built-in front and rear discharge deflector plates
- Adjustable skids with top and side gussets
- Contour float/fixed headstock

## Gearbox, driveshaft & clutch

- Quality Jarrett Australian-made gearbox
- High speed ratio: 1:1.95 (EHD210: 1:1.5)
- Gearbox rating: 83kw (110hp)
- Series 8 telescopic triangular shaft
- 4 friction plate 200mm clutch

## Cutter disc

- Tapered splined hub
- Fabricated cutting disc for maximum strength and shock protection
- Spring steel EHD Jarrett slasher blades
  - 3 x 100x12mm, step
- Jarrett 'taper lock' blade bolts

## Options

- Front and/or rear rubber deflector extension guards
- Front and/or rear chain guard set
- Solid rubber, dual rear wheel kit
- Galvanised body

## Specifications

Model	Width	Weight	Gbox	Min pwr	Mount	Link	Cut height	Tip speed
EHD150	1.50 m	580 kg	110 hp	50 hp	Centre	Cat 2	10–85 mm	81.9 m/s (16,116 ft/min)
EHD180	1.80 m	680 kg	110 hp	60 hp	Centre	Cat 2	10–85 mm	98.2 m/s (19,330 ft/min)
EHD210	2.10 m	780 kg	110 hp	70 hp	Centre	Cat 2	10–85 mm	89.1 m/s (17,535 ft/min)



## Jarrett Implements Pty Ltd

(ABN 81 000 582 918)

244 New Line Road, DURAL NSW 2158 Australian tel: 02 9651 2166 fax: 02 9651 3069

International tel: +61 2 9651 2166 International fax: +61 2 9651 3069

Email: agsales@jarrett.net.au

\* Due to continuous development, specifications may change without notice or obligation to upgrade superceded models.

Sold and serviced by: