

JARRETT H SERIES SLASHERS*

"With an engineering background, I consider Jarrett products to be very good. We've transformed a rough paddock into a park-like area with our Jarrett slasher!"

— H. H. Mitchell, Hobby farmer



The HR150 roller slasher (left hand offset mounting)



The HD180G slasher (centre mounting with galvanised deck)

General construction

- 5mm steel deck sheet
- 12mm steel reinforced gearbox plate (17mm total thickness for gearbox mounting)
- Obstruction free top deck (no debris collection points)
- Obstruction free cutting chamber
- Strong A frame with clevis hitch and Category 1/2 lifting pins
- Built-in front and rear discharge deflector plates
- Adjustable skids with top gusset

Gearbox, driveshaft & clutch

- HM: Quality gearbox
- HD, HR: Quality Jarrett Australian-made gearbox
- High speed: 1:1.97 ratio (HD210: 1:1.47 ratio)
- Gearbox rating 57kw/75hp (HDL: 34kw/45hp)
- Series 6 telescopic triangular driveshaft
- 2 friction plate 200mm clutch

Cutter beam

- Tapered splined hub
- Fabricated cutting beam for maximum strength
- 2 spring steel HD Jarrett slasher blades (75x10mm, step and twist)

Options

- Front and/or rear rubber deflector extension guards
- Front and/or rear chain guard set
- Solid rubber, rear wheel kit (suit HM150, HD150)
- Solid rubber, dual rear wheel kit (suit HM150/180, HD150/180/210)
- Galvanised body
- 3 Blade disc base (suit HD)

Specifications

Model	Width	Weight	Gbox	Min pwr	Mount	Link	Cut height	Tip speed
HM150	1.50 m	350 kg	75 hp	45 hp	LH offset	Cat 1/2	10–85 mm	81.9 m/s (16,116 ft/min)
HM180	1.80 m	430 kg	75 hp	55 hp	Centre	Cat 1/2	10–85 mm	98.2 m/s (19,330 ft/min)
HR150	1.50 m	500 kg	75 hp	45 hp	LH offset	Cat 1/2	10–85 mm	81.9 m/s (16,116 ft/min)
HR180	1.80 m	580 kg	75 hp	55 hp	Centre	Cat 1/2	10–85 mm	98.2 m/s (19,330 ft/min)
HD150L	1.50 m	350 kg	45 hp	35 hp	LH offset	Cat 1/2	10–85 mm	81.9 m/s (16,116 ft/min)
HD150	1.50 m	380 kg	75 hp	45 hp	LH offset	Cat 1/2	10–85 mm	81.9 m/s (16,116 ft/min)
HD180	1.80 m	450 kg	75 hp	55 hp	Centre	Cat 1/2	10–85 mm	98.2 m/s (19,330 ft/min)
HD210	2.10 m	520 kg	75 hp	65 hp	Centre	Cat 1/2	10–85 mm	89.1 m/s (17,535 ft/min)



Jarrett Implements Pty Ltd

(ABN 81 000 582 918)

244 New Line Road, DURAL NSW 2158 Australian tel: 02 9651 2166 fax: 02 9651 3069

International tel: +61 2 9651 2166 International fax: +61 2 9651 3069

Email: agsales@jarrett.net.au

* Due to continuous development, specifications may change without notice or obligation to upgrade superceded models.

Sold and serviced by: