

JARRETT M SERIES SLASHERS*

"After 40 years of use, my Jarrett implements are still working well."

— Ken Gregory, Hobby farmer



The MD135 slasher (left hand offset mounting)



The MDX180 slasher (centre mounting)

General construction

- 5mm steel deck sheet
- 5mm steel reinforced gearbox plate (10mm total thickness for MD gearbox mounting)
- 10mm steel reinforced gearbox plate (15mm total thickness for MDX gearbox mounting)
- Obstruction free top deck (no debris collection points)
- Obstruction free cutting chamber
- Strong A frame with gusset and Category 1 lifting pins
- Built-in front and rear steel discharge deflector plates
- Adjustable skids

Gearbox, driveshaft & clutch

- Quality gearbox
- High speed: 1:1.97 ratio
- MD gearbox rated at 30kw (40hp)
- MDX gearbox rated at 57kw (75hp)
- MD: Series 4 telescopic triangular driveshaft
- MDX: Series 6 telescopic triangular driveshaft
- MD: Two friction plate 150mm clutch
- MDX: Two friction plate 200mm clutch

Cutter beam

- Tapered splined hub
- Fabricated cutting beam for maximum strength
- MD series: 2 spring steel Jarrett pasture blades (50x7mm, step and twist)
- MDX series: 2 spring steel Jarrett slasher blades (75x10mm, step and twist)

Options

- Front and/or rear rubber deflector extension guards
- The manufacturer is happy to discuss your particular requirements

Specifications

Model	Width	Weight	Gbox	Min pwr	Mount	Link	Cut height	Tip speed
MD120	1.20 m	230 kg	40 hp	20 hp	LH offset	Cat 1	10–85 mm	65.5 m/s (12,890 ft/min)
MD135	1.35 m	260 kg	40 hp	25 hp	LH offset	Cat 1	10–85 mm	73.7 m/s (14,500 ft/min)
MD150	1.50 m	290 kg	40 hp	35 hp	LH offset	Cat 1	10–85 mm	81.9 m/s (16,116 ft/min)
MDX150	1.50 m	330 kg	75 hp	45 hp	LH offset	Cat 1	10–85 mm	81.9 m/s (16,116 ft/min)
MDX180	1.80 m	400 kg	75 hp	55 hp	Centre	Cat 1	10–85 mm	98.2 m/s (19,330 ft/min)



Jarrett Implements Pty Ltd

(ABN 81 000 582 918)

244 New Line Road, DURAL NSW 2158 Australian tel: 02 9651 2166 fax: 02 9651 3069

International tel: +61 2 9651 2166 International fax: +61 2 9651 3069

Email: agsales@jarrett.net.au

* Due to continuous development, specifications may change without notice or obligation to upgrade superceded models.

Sold and serviced by: